

Main features and functions

Operator Display

5.2 inch wide color LCD screen with 2 lines X 16 characters and a 1 line numeric display offer the operator a clear view of transaction information.

Use 5 selectable colors for the LCD backlight to illuminate the operator display to fit the customer's environment. A scheduler function makes it possible to switch the backlight color, price levels and automate your report printing at different times of the day or week.

Tilt mechanism for optimum viewing

Receipt/Journal Printer

A 2-station fast (14 lines per sec.), silent and wide (58mm) printer offers the option of using the built-in auto cutter or tear bar to generate customer receipt. The TE-3000 printer also offers:

- Drop-in paper loading for easy handling of paper replacement
- Graphic and Watermark logo printing for professional presentation of customer receipts

Communications

The TE-3000's 3 serial ports allow various peripheral connections which include:

- Scanner
- External dot matrix and/or thermal printer
- · Slip printer

- Remote customer display
- Scale

PC/modem

• Credit/Debit/EBT interface

An optional Arcnet board (IO PB-17) provide register-to-register communications for sales consolidation and program uploading/downloading. Up to 32 terminals can be connected via CAT5 or the Casio inline network.

Storage Device

The TE-3000's innovated use of CF card (Compact Flash Card) technology gives the ability to save and restore program information.

Functionality

- Scan up to 25,000 items
- Food Stamps
- Bottle link

- Mix & Match discounting
- 3 price levels
- Clerk commission rates

- · Not Found Item file
- PLU stock control
- Daily/Weekly/Monthly reporting

- 30 departments (expandable to 99)
- Up to 4 cash drawers
- Time & Attendance

- 512K RAM standard (expandable to 1.5MB)
- Suspend/resume
- 99 Clerks
- Clerk Detail Tracking (Up to 200 totalizers)
- Sub-department/Group Linking

Options

- RK-3 memory board for 1MB
- Multi-Drawers kit (MDL-11) 3 Additional Drawers
- I/O-PB-17 (IRC board)
- · Dallas Clerk Key Kit



• The LCD display can be tilted to the optimal reading angle.



· Drop-in paper-loading for quick, easy paper roll changes



· CF card interface for fast, simple data transfer

Specifications

Electrical Specifications		
		120V 220V 23V 240V
Power consumption	In operation	Max. 0.9A 0.5A 0.5A 0.5A
	stand-by	Max. 0.20A 0.11A 0.11A 0.10A
Memory protection	Back-up battery	VL3032/1F2 (Vanadium lithium battery
	Back-up period	90 days (25 °C)
	Battery life	Replace the battery every 5 years.
	Recharge time	48 hours (full charge)
Main components		
Flash Rom	Capacity	2Mbytes
Thermal printer	Printer method	Impression heat line dot
	Head specification	Total dot number: 432 dots/dot line
		Dot pitch: Length 8 dots/mm
		Wide 8 dots/mm
	Paper cut	Auto-paper cut
	Paper supply method	Drop-in paper loading
Roll paper	Туре	Heat-sensitive paper
	Size	57.5±0.5mm
	Roll diam	φ83 or less
	Thickness	75±3µm